




## MODEL: R1113 SINGLE ROLLER COATER

This machine is to coat the UV primer, sealer, with color or without color, for base or for top coating;

it can do as different process, different coat thickness, and the flat and smooth surface effect.



Effective working width:	0-1320mm				
2. Effective working thickness::	2-80mm				
3. Min length of item:	300mm				
4. Conveyor speed:	0-25m/min				
5. Quantity of paint:	10-15g/m²				
6. Power:	3.75KW + laquer heating				
7. Machine size:	1000mm×2575mm×1700mm		Y		
8. Application roller:	Size:	Material: Rubber	Specification:40-45 shore	Quantity:1 pcs	
9. Doctor roller:	Size: ⊄ 180×1450 mm	Material: 45#seamless steel	Specification: plating hard chromium	Quantity:1 pcs	
10. Support roller:	Size: ⊄200×1320 mm	Material: 45#seamless steel	Specification: chrome plated	Quantity:1 pcs	
11. Conveyor roller::	Size: ⊄130×1330 mm	Material: 45#seamless steel	Specification: chrome plated	Quantity:2 pcs	
12. Up-down system:	Mode: Automatic lifting	3 sets reducer for lifter	Lift table: cast iron dovetail & groove		





13. Recycle system:	stainless steel return chute	4" diaphragm pump	3KW stainless steel heating barrel				
14. Main part of machine:	Frame: 18mm Steel plate	Casting	Belt: 3mm PVC flat belt				
	1 sets blade holder	1 pcs 0.15mm blade made in tungsten steel					
Electric equipment:							
15. Motor for roller:	Brand: Siemens	Specification: 1.5KW * 2 sets ,	Quantity: 3 sets				
16. Reducer for roller:	Brand: RV	Specification: 75# 60:1*1 sets, 75#	Quantity: 3 sets				
17. Reducer for lifting:	Brand: Jiangsheng	Specification: TY-3T 12:1 (one set include 3 reducers)		Quantity: 1 sets			
18. Inverter:	Brand: Siemens	Specification: 1.5KW * 2 sets, 0.75KW * 1 sets		Quantity: 3 sets			
19. HMI:	Brand: Siemens						
20. Low-voltage apparatus:	Brand: Siemens						
21. Safety automatic	If any machine of the line fault , all machine before fault stop conveyor, and up automatic , protect itself.						

